

Technical Specifications

Control protocols: Art-Net, Kling-Net&DMX

Electronics in full digital control with front panel and LED display

Automatic self-test function even in the absence of a console

Control output: RJ45 connector

Data Connection: two Ethernet connectors (RJ45) for data source and secondary driver link

Universes: 4 universes

Channels for universe: 480

Power supply: AC 100-240V, 50/60Hz(Meanwell Brand)

Maximum consumption: 320W

Steel body

Internal Protection: IP20

Weight: 2,5 kg

Dimensions (WxHxD): 483x54x150 mm

DMX Value:

8CHs Model	Function	Numerical value
CH1	Master Dimmer	0-255
CH2	Strobe – Slow to Fast	0-255
CH3	Red	0-255
CH4	Green	0-255
CH5	Blue	0-255
CH6	Auto Programs1-15	0-255(when using this Ch,the Ch1/CH2 must me at the value of 0
CH7	Auto Programs 16-30	0-255(when using this Ch,the Ch1/CH2 must me at the value of 0
CH8	Auto Program Speed – Slow to Fast	0-255

480CHs Model	Function	Numerical value
CH1	RED color of Led 1	0-255
CH2	Green Color of Led1	0-255
CH3	Blue Color of led1	0-255
CH4-480	Colors of each leds(Total 160pcs leds)	0-255