

## 3W\*54 Waterproof PAR

### Operating instruction

Thank you for purchasing this LED products. This LED product is noble and practical. It also has the features in elegant appearance, reasonable design in circuit, fewer-consumes in electricity, high brightness, good decoration effect and so on. It may use in the outdoor stage, the building, the square, the limestone cave's background dyeing or making the frequency dodge effect.

This product may use 90-250V city electricity, and are universal in the world

This lamps and lanterns use 54, each power is 1W or the 3W ultra Gao Liang light emitter diode, and its brightness can compare with the 500 tiles above, and does not need to install the chromo paper or to change the chroma, red, green, blue color light emitter diode may mix seven mainly colors and several hundreds of different colors, brightness color, moreover the lamps and lanterns may adjust the light voluntarily, does not need the expensive silicon box, normal use, the light bulb life surpasses for three years.

When using lamps and lanterns, it will give off heat, forbidden touching, against scalding, This lamps and lanterns should prevent overheated. The temperature should be situated between 5-45°C when it used. After closing the lamps and lanterns' power source, it should wait for several minutes until its natural cooling. This lamps and lanterns must install in the well ventilating place. The lamp body should not cover by other goods or the package. Around the lamps and lanterns in 1 meter cannot lay aside any flammable, explosive or heating chemical goods.

The lamps and lanterns has the high interior tension circuit, the laymen please do not turn on the lamps and lanterns lid, by against electric shock..

Before the circular energization, please check out careful inspection lamp body, the power line and the poison-pen letter, insert prime, guarantees perfectly. If the power line damaged, it may possibly causes drain, and other serious accident. The laymen can not make the revision or the service work arbitrarily to this lamps and lanterns. If this kind of situation happened, and caused the adverse consequences, we don't undertake any responsibility.



### product warranty card

name | model

manufact | buy date  
date

Company name: Address: Tel:
-----------------------------------

contact person: Tel: Seal:
----------------------------------

Note: The above blank must be fill in, seal truthfully by

the end-user, (warranty period and terms, as follow)

Warranty: one year

Warranty terms:

1, failures at the warranty period In the normal State, In

Accordance with the terms of this warranty, To produce the warranty

card and purchase notes (photocopy), enjoy free maintenance service

In the designated service center or the manufacturer.

2, during the warranty, there will Implementation of the paid

Service, as follow:

- (1) Can not show the valid warranty card
- (2) Omission, alteration or no sales shop name on the warranty Card.
- (3) The fault or damage as the non-resistance
- (4) The fault or damage as the transport, unloading
- (5) The fault or damage as not follow the instructions
- (6) Disassemble the light Without factory authorization or non-professionals
- (7) Use of non-factory authorized non-matching control system for factory
- (8) Consumables (light bulbs)

### 一： Display panel operation

After turn on show system reset, press Up or DOWN, then press ENTER to save, return to previous menu press ESC (to return)



MANUL UP DOWN ENTER  
菜单 上 下 确定

d001	→	d512	→	4CHmode
A001	→	A512	→	8CHmode
FF01	→	FF99	→	color washlight
CC01	→	CC99	→	color washlight
EE01	→	EE99	→	Manual Color Selection
dEoo	→	dEoo	→	Demo mode
SoUd	→	SoUd	→	Sound modo

### 二： Channel

Channel	VALUE	FUNCTION
CH1	0	Red off
	1-255	dark to light
CH2	0	Green off
	1-255	dark to light
CH3	0	Blue off
	1-255	dark to light
CH4	0	White off
	1-255	dark to light
8CH		
Channel	VALUE	FUNCTION
CH1	0-255	Total dimming
CH2	0	Red off
	1-255	dark to light

CH3	0	Green off
	1-255	dark to light
CH4	0	Blue off
	1-255	dark to light
CH5	0	White off
	1-255	dark to light
CH6	0-255	Strobe from slow to fast
CH7	0-255	Strobe from slow to fast
CH8	0-2	openCH1-CH6
	3-49	strobobflash
	50-100	Color Selection procedure
	101-150	Program tachycardia
	151-200	Process transition
	201-250	Process transition
	251-255	Sound on

### 三： Master- slave Set

2 sets or over 2 sets of same lights connect by the 3 pin signal cable, set any one as the host of demonstration programs or gradual change other lights set to receive address D001.

### 四： Technical Referance

Power Source 1: AC22V/50W/120W/200W

Power Source 2: DC14V/50W/120W/200W

Power Source 3: AC24V/60W/120W/200W

Power Source 4: DC24V/60W/120W/200W

LightSource: 54W/108W/180W LED

Channel: 8个 DMX512control channels

Sound modo, Built-in program, Master-slave control.

Stroboscopic effect, the program selected color, color change.。

